

## TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery  
 Description: FLOTATION RIB 774 is suitable in all free-rolling applications and ideal for trailers and implement machinery. It has been designed to provide best handling comfort optimizing the timing of operations as well as farmers' productivity.

**Pattern Name**      **FLOTATION RIB 774**

Version: STANDARD  
 US Code: 94006618  
 Type: TL  
 Tire Size: 550/60 - 22.5  
 PR: 16



Dimensions (U/M US Standard)  
 Section Width (in): 21.7  
 Overall Diameter (in): 48.8  
 Static Loaded Radius (in): 21.3  
 Rolling Circumference (in): 146.7  
 Rim Rec: AG 16.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	35	38	41
5 FR	15370	16110	16820
10 FR	13830	14490	15130
20 FR	12300	12890	13460
25 FR	10980	11510	12010
30 FR	9880	10360	10750
5 DW	10570	11080	11570
10 DW	9510	9980	10420
20 DW	8450	8860	9260
25 DW	7550	7910	8270
30 DW	6800	7120	7390

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%