

**TECHNICAL SPECIFICATION**

Applications: Trailer / Implement Machinery  
 Description: FLOTATION RIB 774 is suitable in all free-rolling applications and ideal for trailers and implement machinery. It has been designed to provide best handling comfort optimizing the timing of operations as well as farmers' productivity.

**Pattern Name FLOTATION RIB 774**

Version: STANDARD  
 US Code: 94006632  
 Type: TL  
 Tire Size: 600/55 - 22.5  
 PR: 16



Dimensions (U/M US Standard)  
 Section Width (in): 23.6  
 Overall Diameter (in): 48.4  
 Static Loaded Radius (in): 21.3  
 Rolling Circumference (in): 146.3  
 Rim Rec: AG 20.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	32	35	38
5 FR	16240	17080	17900
10 FR	14620	15380	16110
20 FR	12980	13670	14320
25 FR	11600	12200	12790
30 FR	10440	10980	11680
5 DW	11200	11770	12350
10 DW	10090	10590	11110
20 DW	8960	9420	9880
25 DW	8000	8410	8820
30 DW	7200	7570	8050

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%