

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Implement Machinery  
 Description                      AW 702 has been developed for implement machinery and trailers in soil tillage and transport applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs.

**Pattern Name                      AW 702**  
 Version                              STANDARD  
 US Code                             94009022  
 Type                                 TL  
 Tire Size                            10.0/75 - 15.3  
 PR                                    10



Dimensions (U/M US Standard)  
 Section Width (in)                10.8  
 Overall Diameter (in)            29.9  
 Static Loaded Radius (in)       13.5  
 Rolling Circumference (in)     87.7  
 Rim Rec                             9.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..