

TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery
 Description: AW 702 has been developed for implement machinery and trailers in soil tillage and transport applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs.

Pattern Name **AW 702**
 Version: STANDARD
 US Code: 94009466
 Type: TL
 Tire Size: 11.5/80 - 15.3
 PR: 14



Dimensions (U/M US Standard)
 Section Width (in): 11.7
 Overall Diameter (in): 33.2
 Static Loaded Radius (in): 14.6
 Rolling Circumference (in): 97.4
 Rim Rec: 9.00

LOAD CAPACITY TABLE (lbs)

mph / psi	69
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..