

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Implement Machinery  
 Description                      AW 705 has been developed for implement machinery and trailers in soil tillage and transport applications. It is ideal for modern farming both on and off the road. AW 705 is available also in a "special" version, which offers improved durability.

**Pattern Name                      AW 705**  
 Version                              STANDARD  
 US Code                              94009930  
 Type                                      TL  
 Tire Size                              14.0/65 - 16  
 PR                                        14



Dimensions (U/M US Standard)  
 Section Width (in)                13.9  
 Overall Diameter (in)            34.3  
 Static Loaded Radius (in)       15.3  
 Rolling Circumference (in)     100.4  
 Rim Rec                              11.0

**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 58   |
|-----------|------|
| 5 FR      | 8180 |
| 15 FR     | 6960 |
| 20 FR     | 6550 |
| 25 FR     | 5840 |

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..