

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Implement Machinery  
 Description                      AW 909 has been developed for soil tillage and transport applications with implement machinery and trailers. It is ideal for modern farming both on and off the road. Besides, it provides a high level of handling comfort.

**Pattern Name                      AW 909**  
 Version                              STANDARD  
 US Code                              94010424  
 Type                                      TL  
 Tire Size                              10.0/75 - 15.3  
 PR                                        12



Dimensions (U/M US Standard)  
 Section Width (in)                10.8  
 Overall Diameter (in)            29.9  
 Static Loaded Radius (in)       13.5  
 Rolling Circumference (in)     87.7  
 Rim Rec                                9.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	68
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..