

TECHNICAL SPECIFICATION

Applications Trailer / Implement Machinery
 Description AW 909 has been developed for soil tillage and transport applications with implement machinery and trailers. It is ideal for modern farming both on and off the road. Besides, it provides a high level of handling comfort.

Pattern Name AW 909
 Version STANDARD
 US Code 94010783
 Type TL
 Tire Size 15.0/55 - 17
 PR 12



Dimensions (U/M US Standard)
 Section Width (in) 15.4
 Overall Diameter (in) 33.5
 Static Loaded Radius (in) 14.8
 Rolling Circumference (in) 98
 Rim Rec 13.00
 Rim Alt 13
 ECE E11-106R-003515

LOAD CAPACITY TABLE (lbs)

mph / psi	45
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..