

## TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery  
 Description: RIB 774 (B) is a low section implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications.

**Pattern Name**      **RIB 774 (B)**  
 Version: STANDARD  
 US Code: 94010974  
 Type: TT  
 Tire Size: 200/60 - 14.5  
 PR: 10



Dimensions (U/M US Standard)  
 Section Width (in): 8.3  
 Overall Diameter (in): 24.0  
 Static Loaded Radius (in): 10.9  
 Rolling Circumference (in): 70.3  
 Rim Rec: 6.75  
 Rim Alt: 4.50 E ; 5.50 F

**LOAD CAPACITY TABLE (lbs)**

mph / psi	73
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..