

TECHNICAL SPECIFICATION

Applications Rotor Rake / Tedder / Mower
 Description LG RIB is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages and ensures a long product life. LG RIB is available in an "aramid-belted" version for users who need strengthened puncture resistance.

Pattern Name **LG RIB**
 Version ARAMID BELTED
 US Code 94013012
 Type TL
 Tire Size 13 X 5.00 - 6
 PR 6

Dimensions (U/M US Standard)
 Section Width (in) 5.0
 Overall Diameter (in) 12.8
 Static Loaded Radius (in) 5.7
 Rolling Circumference (in) 37.1
 Rim Rec 3.50 A



LOAD CAPACITY TABLE (lbs)

mph / psi	60
10	560

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..