

TECHNICAL SPECIFICATION

Applications Implement Machinery
 Description TR 360 is suitable for implement machinery in hay harvesting and lawn and garden applications. The particular tread design along with the casing structure provides excellent stability in all field conditions and ensures a long tire life-cycle.

Pattern Name **TR 360**
 Version STANDARD
 US Code 94013104
 Type TL
 Tire Size 18 X 7 - 8
 PR 6



Dimensions (U/M US Standard)
 Section Width (in) 7.1
 Overall Diameter (in) 18.1
 Static Loaded Radius (in) 8.0
 Rolling Circumference (in) 52.5
 Rim Rec 5.5

LOAD CAPACITY TABLE (lbs)

mph / psi	46
10	990

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..