

TECHNICAL SPECIFICATION

Applications Trailer / Light Truck / Compact Utility Tractor
 Description BK 208 is suitable for transport applications on trailers and light trucks. It is a considerably durable and reliable tire for both in-the-field and on-the-road usage.

Pattern Name BK 208
 Version STANDARD
 US Code 94013258
 Type TT
 Tire Size 7.50 - 16
 PR 16



Dimensions (U/M US Standard)
 Section Width (in) 8.3
 Overall Diameter (in) 31.9
 Rim Rec 6.00 G

LOAD CAPACITY TABLE (lbs)

mph / psi	-
-	-
-	-

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..