

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for backhoe loaders, compact loaders and telehandlers. Its extra wide lugs provide excellent grip and great stability in lift operations. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

Pattern Name **RT 747 AGRO INDUSTRIAL**

Version STANDARD
US Code 94016815
Type TL
Tire Size 460/70 R 24
LI/SS 152 A8/149 B
TMPH 1

Dimensions (U/M US Standard)

Section Width (in) 18.3
Overall Diameter (in) 49.4
Static Loaded Radius (in) 21.9
Rolling Circumference (in) 151.2
SRI 575
Rim Rec DW 15 L
Rim Alt DW 14 L ; DW 16 L
ECE E11-106R-004071



LOAD CAPACITY TABLE (lbs)

mph / psi	17	23	29	35	41	46
30	3370	4160	4870	5670	6580	7160
25	3680	4540	5320	6180	6970	7830
20	3940	4860	5700	6610	7450	8380
15	4080	5040	5910	6870	7730	8690
5 Cyc	5520	6810	7980	9270	10450	11740
Static	7730	9530	11180	12980	14630	16430