

TECHNICAL SPECIFICATION

Applications Telehandler / Compact Loader / Backhoe Loader

Description RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for backhoe loaders, compact loaders and telehandlers. Its extra wide lugs provide excellent grip and great stability in lift operations. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

Pattern Name **RT 747 AGRO INDUSTRIAL**

Version STANDARD
US Code 94016822
Type TL
Tire Size 500/70 R 24
LI/SS 157 A8/154 B

Dimensions (U/M US Standard)

Section Width (in) 19.1
Overall Diameter (in) 52.0
Static Loaded Radius (in) 23.0
Rolling Circumference (in) 155.5
SRI 625
Rim Rec DW 16 L
Rim Alt DW 15 L ; DW 18 L



LOAD CAPACITY TABLE (lbs)

mph / psi	17	23	29	35	41	44
30	3890	4790	5620	6540	7360	8270
25	4280	5280	6180	7190	8090	9090
20	4570	5640	6610	7690	8660	9730
15	4750	5850	6870	7980	8980	10100
5 Cyc	6420	7910	9280	10780	12150	13650
Static	8980	11080	12980	15090	17000	19100