

TECHNICAL SPECIFICATION

Applications Trailer / Implement Machinery
 Description ST 180 is a road-oriented tire developed for soil tillage and transport applications with trailers and implement machinery. Its specific tread pattern ensures a long tire life-cycle due to reduced wear and contributes to significant fuel savings.

Pattern Name ST 180
 Version STANDARD
 US Code 94018093
 Type TL
 Tire Size ST 175/80 D 13
 PR 6



Dimensions (U/M US Standard)
 Section Width (in) 6.9
 Overall Diameter (in) 24.4
 Static Loaded Radius (in) 11.3
 Rolling Circumference (in) 72.6
 Rim Rec 5 J
 Rim Alt 4½ J ; 5½ J ; 6 J

LOAD CAPACITY TABLE (lbs)

mph / psi	-
-	-

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..