

## TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler  
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name AS 504**  
 Version STANDARD  
 Type TT  
 Tire Size 10.0/75 - 15.3  
 PR 8



Dimensions (U/M US Standard)  
 Section Width (in) 10.4  
 Overall Diameter (in) 30.7  
 Static Loaded Radius (in) 13.6  
 Rolling Circumference (in) 90  
 SRI 360  
 Rim Rec 9.00

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler  
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

### LOAD CAPACITY TABLE (lbs)

mph / psi	45
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

\* Tolerances: Overall Diameter  $\pm$  2% | Section Width  $\pm$  2% | Rolling Circumference  $\pm$  2.5%