

TECHNICAL SPECIFICATION

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version: STANDARD

US Code: 94018567

Type: TL

Tire Size: 10.0/75 - 15.3

PR: 10



Dimensions (U/M US Standard)

Section Width (in): 10.4

Overall Diameter (in): 30.7

Static Loaded Radius (in): 13.6

Rolling Circumference (in): 90

SRI: 360

Rim Rec: 9.00

ECE: E4-106R-001812

LOAD CAPACITY TABLE (lbs)

| mph / psi | 57 |
|-----------|------|
| 5 FR | 4780 |
| 15 FR | 4070 |
| 20 FR | 3820 |
| 25 FR | 3420 |
| 5 DW | 3360 |
| 15 DW | 2850 |
| 20 DW | 2690 |
| 25 DW | 2400 |

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%