

## TECHNICAL SPECIFICATION

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name** **AS 504**

Version STANDARD

Type TL

Tire Size 10.5/80 - 18

PR 10



**Dimensions (U/M US Standard)**

Section Width (in) 10.8

Overall Diameter (in) 35.7

Static Loaded Radius (in) 15.9

Rolling Circumference (in) 104.6

SRI 425

Rim Rec W 9

Rim Alt 9 ; W 8

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**LOAD CAPACITY TABLE (lbs)**

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%