

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version STANDARD

Type TT

Tire Size 11.5/80 - 15.3

PR 8



Dimensions (U/M US Standard)

Section Width (in) 11.4

Overall Diameter (in) 34.1

Static Loaded Radius (in) 15.0

Rolling Circumference (in) 100

SRI 410

Rim Rec 9.00

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	39
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750
5 DW	3640
15 DW	3100
20 DW	2910
25 DW	2600

* Tolerances: Overall Diameter $\pm 2\%$ | Section Width $\pm 2\%$ | Rolling Circumference $\pm 2.5\%$