

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version STANDARD

Type TT

Tire Size 11.5/80 - 15.3

PR 12



Dimensions (U/M US Standard)

Section Width (in) 11.4

Overall Diameter (in) 34.1

Static Loaded Radius (in) 15.0

Rolling Circumference (in) 100

SRI 410

Rim Rec 9.00

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

| mph / psi | 59 |
|-----------|------|
| 5 FR | 6720 |
| 15 FR | 5720 |
| 20 FR | 5380 |
| 25 FR | 4810 |
| 5 DW | 4780 |
| 15 DW | 4070 |
| 20 DW | 3820 |
| 25 DW | 3420 |

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%