

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version STANDARD
 Type TL
 Tire Size 15.5/80 - 24
 PR 16



Dimensions (U/M US Standard)

Section Width (in) 15.1
 Overall Diameter (in) 49.7
 Static Loaded Radius (in) 22.3
 Rolling Circumference (in) 143.9
 SRI 600
 Rim Rec W 12
 Rim Alt W 13 ; W 14 L

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	58
5 FR	15050
15 FR	12790
20 FR	12040
25 FR	10750
5 DW	10650
15 DW	9050
20 DW	8520
25 DW	7610

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%