

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 US Code 94019144
 Type TT
 Tire Size 5.00 - 15
 PR 4



Dimensions (U/M US Standard)

Section Width (in) 5.5
 Overall Diameter (in) 25.9
 Static Loaded Radius (in) 12.1
 Rolling Circumference (in) 77
 SRI 310
 Rim Rec 3.50 D
 Rim Alt 3.00 D ; 4.00 E ; 4 J

LOAD CAPACITY TABLE (lbs)

| mph / psi | 33 |
|-----------|------|
| 5 FR | 1340 |
| 15 FR | 1150 |
| 20 FR | 1070 |
| 25 FR | 960 |
| 5 DW | 940 |
| 15 DW | 800 |
| 20 DW | 750 |
| 25 DW | 670 |

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%