

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 US Code 94019168
 Type TT
 Tire Size 6.00 - 16
 PR 6



Dimensions (U/M US Standard)
 Section Width (in) 6.5
 Overall Diameter (in) 28.9
 Static Loaded Radius (in) 13.5
 Rolling Circumference (in) 86.2
 SRI 350
 Rim Rec 4.00 E
 Rim Alt 4.50 E ; 4 1/2 K
 ECE E4-106R-002836

LOAD CAPACITY TABLE (lbs)

mph / psi	41
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520
5 DW	1500
15 DW	1270
20 DW	1200
25 DW	1070

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%