

## TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler  
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name AS 504**

Version STANDARD  
 US Code 94019182  
 Type TT  
 Tire Size 6.5/80 - 12  
 PR 4



Dimensions (U/M US Standard)

Section Width (in) 6.4  
 Overall Diameter (in) 23.9  
 Static Loaded Radius (in) 10.7  
 Rolling Circumference (in) 72.9  
 Rim Rec 5 J  
 Rim Alt 5 JA  
 ECE E11-106R-003440

LOAD CAPACITY TABLE (lbs)

mph / psi	35
5 FR	1540
15 FR	1310
20 FR	1230
25 FR	1100
5 DW	1090
15 DW	930
20 DW	880
25 DW	780

\* Tolerances: Overall Diameter  $\pm$  2% | Section Width  $\pm$  2% | Rolling Circumference  $\pm$  2.5%