

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 US Code 94019328
 Type TT
 Tire Size 7.50 - 16
 PR 8



Dimensions (U/M US Standard)

Section Width (in) 8.2
 Overall Diameter (in) 31.6
 Static Loaded Radius (in) 14.6
 Rolling Circumference (in) 94.2
 SRI 390
 Rim Rec 5.50 F
 Rim Alt 4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
 ECE E4-106R-002633

LOAD CAPACITY TABLE (lbs)

mph / psi	46
5 FR	3460
15 FR	2940
20 FR	2770
25 FR	2470
5 DW	2390
15 DW	2030
20 DW	1920
25 DW	1710

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%