

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 US Code 94019373
 Type TT
 Tire Size 7.50 - 20
 PR 8

Dimensions (U/M US Standard)

Section Width (in) 8.2
 Overall Diameter (in) 35.6
 Static Loaded Radius (in) 16.6
 Rolling Circumference (in) 106.1
 SRI 425
 Rim Rec 5.50 F
 Rim Alt 4.50 E ; 6.00 F ; 5.00 F



LOAD CAPACITY TABLE (lbs)

mph / psi	46
5 FR	3860
15 FR	3260
20 FR	3090
25 FR	2760
5 DW	2700
15 DW	2290
20 DW	2160
25 DW	1930

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%