

## TECHNICAL SPECIFICATION

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name** **AS 504**

Version STANDARD

Type TT

Tire Size 7.50 - 20

PR 8



**Dimensions (U/M US Standard)**

Section Width (in) 8.2

Overall Diameter (in) 35.6

Static Loaded Radius (in) 16.6

Rolling Circumference (in) 106.1

SRI 425

Rim Rec 5.50 F

Rim Alt 4.50 E ; 6.00 F ; 5.00 F

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

### LOAD CAPACITY TABLE (lbs)

mph / psi	46
5 FR	3860
15 FR	3260
20 FR	3090
25 FR	2760
5 DW	2700
15 DW	2290
20 DW	2160
25 DW	1930

\* Tolerances: Overall Diameter  $\pm$  2% | Section Width  $\pm$  2% | Rolling Circumference  $\pm$  2.5%