

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504
 Version STANDARD
 Type TT
 Tire Size 7.5L - 15
 PR 6



Dimensions (U/M US Standard)
 Section Width (in) 8.3
 Overall Diameter (in) 30.1
 Static Loaded Radius (in) 13.9
 Rolling Circumference (in) 89.8
 Rim Rec 6 LB
 Rim Alt 5 K ; 5 1/2 J ; 5 1/2 K

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	45
5 FR	3170
15 FR	2700
20 FR	2550
25 FR	2270
5 DW	2250
15 DW	1920
20 DW	1810
25 DW	1610

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%