

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name **AS 504**

Version SPECIAL

Type TL

Tire Size 15.5/80 - 24

PR 14



Dimensions (U/M US Standard)

Section Width (in) 15.1

Overall Diameter (in) 49.7

Static Loaded Radius (in) 22.3

Rolling Circumference (in) 143.9

SRI 600

Rim Rec W 12

Rim Alt W 13; W 14 L

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	51
5 FR	13890
15 FR	11810
20 FR	11110
25 FR	9920
5 DW	9720
15 DW	8270
20 DW	7780
25 DW	6940

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%