

## TECHNICAL SPECIFICATION

**Applications** Compact Loader / Compact Dumper / Backhoe Loader

**Description** AT 603 is a bias agro-industrial tire for backhoe loaders, compact loaders and compact dumpers in digging and loading applications. AT 603 has been engineered to ensure great traction on drive wheels providing the best performance on and off the road. The AT 603 "special" version offers improved cut and chip resistance while the "HD" version is ideal for heavy-duty service.

**Pattern Name** **AT 603**

Version STANDARD  
 US Code 94019526  
 Type TL  
 Tire Size 10.5/80 - 18  
 PR 10



**Dimensions (U/M US Standard)**

Section Width (in) 10.8  
 Overall Diameter (in) 35.7  
 Static Loaded Radius (in) 15.9  
 Rolling Circumference (in) 104.6  
 SRI 425  
 Rim Rec W 9  
 Rim Alt W 8 ; 9

**LOAD CAPACITY TABLE (lbs)**

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%