

TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery / Compact Dumper
 Description: FLOTATION TR 675 is best suited for soil tillage operations and transport. It fits trailers, compact dumpers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction remaining gentle on the ground to prevent crop damages.

Pattern Name **FLOTATION TR 675**

Version: STANDARD
 US Code: 94019786
 Type: TL
 Tire Size: 500/60 - 22.5
 PR: 12



Dimensions (U/M US Standard)
 Section Width (in): 19.7
 Overall Diameter (in): 46.5
 Static Loaded Radius (in): 21.0
 Rolling Circumference (in): 138
 Rim Rec: AG 16.00
 Rim Alt: 15.00 ; 17.00
 ECE: E4-106R-002314

LOAD CAPACITY TABLE (lbs)

mph / psi	22	29	35
5 FR	9680	11450	12730
10 FR	8710	10310	11460
20 FR	7740	9160	10180
25 FR	6910	8180	9090
30 FR	6220	7360	8270
5 DW	6800	8040	8950
10 DW	6130	7230	8060
20 DW	5450	6440	7160
25 DW	4860	5740	6390
30 DW	4380	5170	5840

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%