

TECHNICAL SPECIFICATION

Applications: Trailer / Implement Machinery / Compact Dumper
 Description: FLOTATION TR 675 is best suited for soil tillage operations and transport. It fits trailers, compact dumpers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction remaining gentle on the ground to prevent crop damages.

Pattern Name **FLOTATION TR 675**

Version: STANDARD
 US Code: 94019816
 Type: TL
 Tire Size: 550/60 - 22.5
 PR: 16



Dimensions (U/M US Standard)

Section Width (in): 21.7
 Overall Diameter (in): 49.6
 Static Loaded Radius (in): 21.5
 Rolling Circumference (in): 143.3
 Rim Rec: AG 16.00
 ECE: E11-106R-004379

LOAD CAPACITY TABLE (lbs)

mph / psi	35	38	41
5 FR	15370	16110	16820
10 FR	13830	14490	15130
20 FR	12300	12890	13460
25 FR	10980	11510	12010
30 FR	9880	10360	10750
5 DW	10570	11080	11570
10 DW	9510	9980	10420
20 DW	8450	8860	9260
25 DW	7550	7910	8270
30 DW	6800	7120	7390

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%