

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94021376
 Type TL
 Tire Size 540/65 R 28
 LI/SS 149 D/152 A8



Dimensions (U/M US Standard)

Section Width (in) 20.9
 Overall Diameter (in) 55.6
 Static Loaded Radius (in) 25.3
 Rolling Circumference (in) 167.4
 SRI 675
 Rim Rec W 16 L
 Rim Alt W 18 L
 ECE E4-106R-000650
 TRA Code R-1W

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3440	4010	4520	5020	5520	5950	6590	7150
30	3620	4220	4750	5280	5800	6250	6930	7530
25	3760	4390	4940	5480	6030	6500	7210	7830
20	3970	4620	5200	5780	6350	6840	7590	8240
5 LT	4620	5380	6050	6720	7400	7970	8840	9600
5 HT	3970	4620	5200	5780	6350	6840	7590	8240