

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name**      **AGRIMAX RT 855**

Version                    STANDARD  
 US Code                 94021543  
 Type                      TL  
 Tire Size                 280/85 R 28  
 LI/SS                     118 A8/B



**Dimensions (U/M US Standard)**

Section Width (in)      11.5  
 Overall Diameter (in)    46.7  
 Static Loaded Radius (in) 21.5  
 Rolling Circumference (in) 140.1  
 SRI                         575  
 Rim Rec                  W 10  
 Rim Alt                    W 9

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	1610	1860	2130	2390	2660	2910
25	1610	1860	2130	2390	2660	2910
20	1720	2010	2280	2570	2840	3120
5 LT	2150	2500	2850	3210	2560	3900
5 HT	1720	2010	2280	2570	2840	3120