

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name      AGRIMAX RT 855**

Version: STANDARD  
 US Code: 94021574  
 Type: TL  
 Tire Size: 320/85 R 28  
 LI/SS: 124 A8/B

Dimensions (U/M US Standard)  
 Section Width (in): 13.0  
 Overall Diameter (in): 49.4  
 Static Loaded Radius (in): 22.4  
 Rolling Circumference (in): 147.4  
 SRI: 600  
 Rim Rec: W 11  
 Rim Alt: W 9 ; W 10



**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3520
25	1940	2260	2580	2900	3220	3520
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780