

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94021598
 Type TL
 Tire Size 320/85 R 32
 LI/SS 126 A8/B

Dimensions (U/M US Standard)

Section Width (in) 13.0
 Overall Diameter (in) 53.4
 Static Loaded Radius (in) 24.4
 Rolling Circumference (in) 160.7
 SRI 650
 Rim Rec W 11
 Rim Alt W 9 ; W 10



LOAD CAPACITY TABLE (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| 25 | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| 20 | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |
| 5 LT | 2770 | 3220 | 3670 | 4120 | 4570 | 5030 |
| 5 HT | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |