

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name**      **AGRIMAX RT 855**

Version                    STANDARD  
 US Code                 94021765  
 Type                      TL  
 Tire Size                 460/85 R 30  
 LI/SS                    145 A8/B

**Dimensions (U/M US Standard)**

Section Width (in)      18.7  
 Overall Diameter (in)   60.8  
 Static Loaded Radius (in) 26.8  
 Rolling Circumference (in) 178.3  
 SRI                        725  
 Rim Rec                 W 16 L  
 Rim Alt                  W 14 L ; W 15 L



**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	3520	4100	4670	5250	5820	6390
25	3520	4100	4670	5250	5820	6390
20	3770	4390	5000	5620	6240	6840
5 LT	4720	5490	6260	7030	7800	8580
5 HT	3770	4290	5000	5620	6240	6840