

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94021796
 Type TL
 Tire Size 480/80 R 42
 LI/SS 151 A8/B



Dimensions (U/M US Standard)

Section Width (in) 18.9
 Overall Diameter (in) 72.2
 Static Loaded Radius (in) 32.9
 Rolling Circumference (in) 214.9
 SRI 875
 Rim Rec W 16 A ; DD 16 ; DW 16 A
 Rim Alt DD 16 L ; DW 16 L ; W 16 L

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150