

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

**Pattern Name      AGRIMAX RT 955**

Version: STANDARD  
 US Code: 94021840  
 Type: TL  
 Tire Size: 270/95 R 48  
 LI/SS: 144 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 10.8  
 Overall Diameter (in): 68.2  
 Static Loaded Radius (in): 32.3  
 Rolling Circumference (in): 210.7  
 SRI: 825  
 Rim Rec: W 9  
 Rim Alt: W 8 ; W 10

**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64   |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30        | 2410 | 3150 | 3840 | 4200 | 4450 | 4880 | 5310 | 5740 | 6150 | -    |
| 25        | 2410 | 3150 | 3840 | 4200 | 4450 | 4880 | 5310 | 5740 | 6150 | -    |
| 20        | 2580 | 3370 | 4100 | 4500 | 4760 | 5220 | 5690 | 6150 | 6610 | -    |
| 5         | 2880 | 3620 | 4450 | 5280 | 6120 | 6300 | 7040 | 7780 | 8520 | 9260 |