

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94021857
 Type: TL
 Tire Size: 270/95 R 32
 LI/SS: 136 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 52.2
 Static Loaded Radius (in): 24.2
 Rolling Circumference (in): 159.2
 SRI: 625
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
25	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
20	2070	2700	3280	3600	3810	4190	4550	4930	5290	-
5	2300	2900	3560	4230	4890	5040	5630	6230	6820	7410