

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name **AGRIMAX RT 955**

Version STANDARD

US Code 94021871

Type TL

Tire Size 300/95 R 46

LI/SS 148 A8/B

Dimensions (U/M US Standard)

Section Width (in) 11.6

Overall Diameter (in) 68.4

Static Loaded Radius (in) 32.0

Rolling Circumference (in) 209.4

SRI 825

Rim Rec W 9

Rim Alt W 10 ; W 11 ; DW 10 ; DW 11



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52	58	64
30	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
25	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
20	2610	3050	3510	3950	4400	4760	5210	5590	6110	6620	7080	7440	-
10	3000	3510	4020	4530	5050	5470	5990	6420	7010	7610	8120	8540	-
5	3360	3940	4510	5090	5670	6140	6710	7200	7870	8540	9120	9590	10420