

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name      AGRIMAX RT 855**

Version: STANDARD  
 US Code: 94021963  
 Type: TL  
 Tire Size: 320/85 R 20  
 LI/SS: 119 A8/B

Dimensions (U/M US Standard)  
 Section Width (in): 13.0  
 Overall Diameter (in): 41.4  
 Static Loaded Radius (in): 18.4  
 Rolling Circumference (in): 122  
 SRI: 500  
 Rim Rec: W 11  
 Rim Alt: W 9 ; W 10



**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1650 | 1930 | 2190 | 2470 | 2730 | 3000 |
| 25        | 1650 | 1930 | 2190 | 2470 | 2730 | 3000 |
| 20        | 1770 | 2060 | 2360 | 2650 | 2930 | 3220 |
| 5 LT      | 2220 | 2580 | 2940 | 3310 | 3670 | 4020 |
| 5 HT      | 1770 | 2060 | 2360 | 2650 | 2930 | 3220 |