

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

Pattern Name AGRIMAX RT 765

Version STANDARD
 US Code 94022014
 Type TL
 Tire Size 240/70 R 16
 LI/SS 104 A8/B



Dimensions (U/M US Standard)
 Section Width (in) 9.6
 Overall Diameter (in) 29.2
 Static Loaded Radius (in) 13.2
 Rolling Circumference (in) 87.6
 SRI 350
 Rim Rec W 8
 Rim Alt W 8 L ; W 9 L

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	940	1080	1230	1390	1550	1710	1850	1980
25	940	1080	1230	1390	1550	1710	1850	1980
20	1000	1160	1320	1500	1660	1830	1980	2130
5 LT	1260	1440	1660	1870	2080	2300	2490	2670
5 HT	1000	1160	1320	1500	1660	1830	1980	2130