

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for agriculture applications with high-power tractors, ensuring top performance and efficiency. AGRIMAX FORCE is a really comfortable tire for both field operations and road transfers; it actually allows to move without the need for increasing the inflation pressure.

Pattern Name **AGRIMAX FORCE**

Version STANDARD

US Code 94022236

Type TL

Tire Size IF 900/60 R 42

LI/SS 186 D



Dimensions (U/M US Standard)

Section Width (in) 36.1

Overall Diameter (in) 84.5

Static Loaded Radius (in) 37.4

Rolling Circumference (in) 254.2

SRI 1025

Rim Rec DW 30 B

Rim Alt TW 30 B

ECE E4-106R-000812

LOAD CAPACITY TABLE (lbs)

mph / psi*	9	12	15	17	20	23	29	35
45	8760	10100	11620	12950	14480	15820	17710	19060
From 40 to 25	9630	11100	12780	14240	15920	17380	19480	20900
20	10010	11540	13280	14800	16540	18080	20250	21780
12	10390	11980	13790	15380	17180	18770	21030	22620
5	12220	14090	16210	18080	20200	22070	24730	26600
5 Cyc*	13480	15530	17880	19930	22280	24330	27260	29320
5HT	10010	11540	13280	14800	16540	18080	20250	21780

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.