

TECHNICAL SPECIFICATION

Applications Reach Stacker
 Description PORT KING PLUS has been specially designed for reach stackers in intermodal/logistics applications. Its deep tread with sturdy lugs along with the special compound provides an extended tire life-cycle. It is also available with a Groove Crack Resistant tread Compound (GCRC).

Pattern Name PORT KING PLUS

Version GCRC
 US Code 94026593
 Type TL
 Tire Size 18.00 - 25
 PR 40



Dimensions (U/M US Standard)
 Overall Diameter (in) 65.9
 Static Loaded Radius (in) 30.1
 Rolling Circumference (in) 195.1
 Rim Rec 13.00 /2.5
 Rim Alt 15.00/2.5

LOAD CAPACITY TABLE (lbs)

mph / psi	145
5	50625

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..