

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504
 Version STANDARD
 Type TT
 Tire Size 27 X 10 - 15.3
 PR 8



Dimensions (U/M US Standard)
 Section Width (in) 10.2
 Overall Diameter (in) 27.4
 Static Loaded Radius (in) 12.5
 Rolling Circumference (in) 81.5
 Rim Rec 9.00

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

| mph / psi | 45 |
|-----------|------|
| 5 FR | 3010 |
| 15 FR | 2560 |
| 20 FR | 2400 |
| 25 FR | 2150 |
| 5 DW | 2130 |
| 15 DW | 1810 |
| 20 DW | 1710 |
| 25 DW | 1520 |

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%