

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name**      **AGRIMAX RT 855**

Version                    STANDARD  
 US Code                 94027460  
 Type                      TL  
 Tire Size                250/85 R 20  
 LI/SS                    116 A8/B

**Dimensions (U/M US Standard)**

Section Width (in)      9.8  
 Overall Diameter (in)   37.0  
 Static Loaded Radius (in) 16.7  
 Rolling Circumference (in) 110.7  
 SRI                        450  
 Rim Rec                  W 8  
 Rim Alt                    W 7 ; W 9



**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23	29	35
30	1300	1490	1710	1930	2150	2370	2570	2760
25	1300	1490	1710	1930	2150	2370	2570	2760
20	1390	1600	1840	2070	2310	2550	2760	2950
5 LT	1740	2000	2290	2590	2890	3190	3440	3690
5 HT	1390	1600	1840	2070	2310	2550	2760	2950