

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94028139
 Type: TL
 Tire Size: 270/95 R 38
 LI/SS: 140 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 58.2
 Static Loaded Radius (in): 27.4
 Rolling Circumference (in): 177.6
 SRI: 700
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2150	2810	3420	3750	3970	4350	4740	5130	5500	-
25	2150	2810	3420	3750	3970	4350	4740	5130	5500	-
20	2300	3010	3660	4010	4250	4660	5080	5490	5900	-
5	2570	3230	3970	4720	5460	5620	6280	6940	7610	8270