

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94028146
 Type: TL
 Tire Size: 270/95 R 44
 LI/SS: 142 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 10.8
 Overall Diameter (in): 64.3
 Static Loaded Radius (in): 30.1
 Rolling Circumference (in): 196.2
 SRI: 775
 Rim Rec: W 9
 Rim Alt: W 8 ; W 10

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
25	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
20	2450	3200	3890	4270	4510	4950	5390	5830	6260	-
5	2720	3430	4210	5000	5790	5960	6670	7360	8070	8760