

## TECHNICAL SPECIFICATION

Applications                   Trailer / Tanker / Spreader  
 Description                   FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle.

**Pattern Name**           **FL 639**  
 Version                    STANDARD  
 US Code                   94028153  
 Type                        TL  
 Tire Size                  600/50 R 22.5  
 LI/SS                      159 D/170 A8



Dimensions (U/M US Standard)  
 Section Width (in)       24.1  
 Overall Diameter (in)   46.1  
 Static Loaded Radius (in) 20.5  
 Rolling Circumference (in) 141.4  
 SRI                         550  
 Rim Rec                  AG 20.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2820	3260	3690	4450	5190	5910	6660	7340	8090	8780
40	3090	3570	4060	4890	5700	6500	7300	8070	8870	9640
30	3740	4320	4910	5950	6890	7880	8820	9740	10750	11670
25	4230	4890	5560	6700	7800	8930	10040	11070	12170	13230
15	4880	5640	6400	7740	8990	10310	11490	12790	14030	15240
5	5560	6430	7300	8820	10250	11740	13090	14550	15970	17360