

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94028412
 Type TL
 Tire Size 540/65 R 34
 LI/SS 152 D/155 A8

Dimensions (U/M US Standard)

Section Width (in) 20.9
 Overall Diameter (in) 61.7
 Static Loaded Radius (in) 28.0
 Rolling Circumference (in) 186.7
 SRI 750
 Rim Rec W 16 L
 Rim Alt W 18 L
 ECE E4-106R-000652



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3760	4390	4940	5480	6030	6500	7210	7850
30	3960	4610	5180	5760	6340	6830	7570	8220
25	4100	4780	5390	5990	6580	7100	7860	8540
20	4330	5050	5680	6300	6940	7480	8290	9010
5 LT	5040	5890	6610	7350	8090	8720	9660	10490
5 HT	4330	5050	5680	6300	6940	7480	8290	9010